


The potential tsunami threats from the South China Sea and hazard mitigation

Dr. Tso-Ren Wu (吳祚任)
Graduate Institute of Hydrological and Oceanic Sciences
National Central University
國立中央大學水文與海洋科學研究所
tsoren@ncu.edu.tw

Introduction

- The 2011 Tōhoku earthquake was a 9.0-magnitude undersea megathrust earthquake off the coast of Japan that occurred at 14:46 JST on Friday 11 March 2011. The epicenter was approximately 72 kilometers (45 mi) east of the Oshika Peninsula of Tōhoku, with the hypocenter at an underwater depth of approximately 32 km (19.9 mi).
- The earthquake triggered extremely destructive tsunami waves of up to 10 meters that struck Japan minutes after the quake, in some cases traveling up to 10 km inland, with smaller waves reaching many other countries after several hours. Tsunami warnings were issued and evacuations ordered along Japan's Pacific coast and at least 20 other countries, including the entire Pacific coast of North America and South America. (Wiki)
- However, the tsunami height in Taiwan was 12cm reported by CWB.



Questions

- Why the tsunami was so devastated in Japan, and only in Japan?
- will the similar scenario present in Taiwan and in the SCS region?
- Strategies for hazard mitigation of the nearsource tsunami?

Tsunami Propagation Model

COMCOT (Cornell Multi-grid Coupled Tsunami Model)

$$\frac{\partial \eta}{\partial t} + \frac{\partial P}{\partial x} + \frac{\partial Q}{\partial y} = 0 \tag{1}$$

$$\frac{\partial P}{\partial t} + gH \frac{\partial \eta}{\partial x} - f\left(\frac{Q}{H}\right) = 0 \tag{2}$$

$$\frac{\partial Q}{\partial t} + gH \frac{\partial \eta}{\partial y} + f\left(\frac{Q}{H}\right) = 0$$

where: x, y are the horizontal coordinates,

 η is the free-surface displacement,

 $H = \eta + h$ is the total water depth,

h is the still water depth,

P = Hu, Q = Hv are the horizontal

volume discharges,

g is gravity, t is time,

f is the Coriolis coefficient.

(1)
$$\frac{\partial \eta}{\partial t} + \frac{\partial P}{\partial x} + \frac{\partial Q}{\partial v} = 0$$
 (3)

(2)
$$\frac{\partial P}{\partial t} + \frac{\partial}{\partial x} \left(\frac{P^2}{H} \right) + \frac{\partial}{\partial y} \left(\frac{PQ}{H} \right) + gH \frac{\partial \eta}{\partial x} + \tau_x = 0$$
 (4)

$$\frac{\partial Q}{\partial t} + \frac{\partial}{\partial x} \left(\frac{PQ^2}{H} \right) + \frac{\partial}{\partial y} \left(\frac{Q^2}{H} \right) + gH \frac{\partial \eta}{\partial y} + \tau_y = 0$$

where τ_x and τ_y are the bottom frictions.

The bottom friction comes form Manning's formula and is expressed as:

$$\tau_{x} = \frac{gn^{2}}{H^{7/3}}P(P^{2} + Q^{2})^{1/2}, \tau_{y} = \frac{gn^{2}}{H^{7/3}}Q(P^{2} + Q^{2})^{1/2}$$
 (5)

地震參數與巢狀網格

USGS

Epicenter: 38.308 142.383

- MW: 9.0

Depth: 10

Strike= 187 Dip=14 Slip= 68




Epicenter: 37.52 143.05


MW: 9.1

Depth: 20


Strike= 203 Dip=10 Slip= 88


L:450km W:150km d:18m








Simulation Results























































Maximum Wave height

Tsunami Source Characterization for Western Pacific Subduction Zones: A Preliminary Report USGS1 Tsunami Subduction Source Working Group


BOTTOM LINE Hazard appraisal key:


A: High

B: Intermediate

C: Low

D: Not classified





Recently the USGS issued a report assessing the potential risk as a tsunami source along the entire Pacific seduction zones. One highly risk zone is identified along the Manila (Luzon) trench, where the Eurasian plate is actively subducting eastward underneath the Luzon volcanic arc on the Philippine Sea plate.

BOTTOM LINE Hazard appraisal key:


A: High

B: Intermediate

C: Low


D: Not classified

South China Sea Region



The exposure of large population centers bounding the South China Sea to tsunami hazard cannot be understated.


(Megawati et al., 2008)




The GPS geodesy measurements show that the convergence rate across the Megathrust is about 8 cm/year. Yu et al. (1999) used 35 GPS stations on Luzon Island and southern Taiwan to calculate the relative motion between Luzon arc and Eurasia. The observation was conducted for two years, from 1996 to 1998. Relative motion is greatest in northern Luzon at 19N, moving 86-90 mm/yr northwestward. The velocities taper gradually towards the north and south as collision regimes pin both ends of the Megathrust.

GPS data (Yu et al., 1999) indicating motion of the converging Eurasian Plate and the Philippines Sea Plate, where the blue arrows and numbers show raw velocity values (mm/yr) taken from Yu et al. (1999), the red arrow and numbers indicate velocity values (mm/yr) resolved in the direction perpendicular to the trench front, and the black numbers give the rounded values (mm/yr) used for slip estimation.

Estimation of Return period





Mw	Return Period (year)
7.0	6
7.5	19
8.0	63
8.5	205
9.0	667


Source: ANSS 1963-2006


It is significant that since the Spanish colonization of Luzon in the 1560s, no earthquake exceeding magnitude 7.8 has been observed (Repetti, 1946). Conservatively, it can be postulated that very large events on this Megathrust have a recurrence interval exceeding 440 years. Taking a trench-normal convergence velocity of 87 mm/yr, strain of ~38 m would range of plausible scenarios. It is comparable to the 1960 Mw 9.5 Chilean earthquake, in which coseismic slip reached 40 m (Barrientos and Ward, 1990), and larger than 2004 Aceh-Andaman event, which produced 20 m of coseismic slip (Chlieh et al., 2007).


Latitude N Longitude * E


The discretized model for computation of seafloor displacement


Initial free-surface profile























Fault parameters of Manila Megathrust


 Earthquake parameters of the three largest tsunami earthquakes. All three earthquakes have similar length varying from 740 to 1300 km, and similar width varying from 200 to 300 km. The earthquake magnitude ranged from Mw = 9.0 to 9.5. Using all of the information and referring to the fault geometry, a set of hypothetical fault of Manila Megathrust is nailed down.


Date	Location	(Lon,lat)	Mw	Length (km)	Width (km)	Ddislocation (m)	Focal Depth (km)	Maximum water height (m)
1960/5/22	Chile	(74.5,39.5)	9.5	1000	300	No data	60	25
1964/3/28	Alaska	(-147.5,61.1)	9.2	540-740	300	18-22	23	67
2004/12/26	Sumatra	(95.98,3.3)	9	1300	200	20	28.6	50

(Data source: Catalog of Tsunamis in the Pacific Ocean, and Harvard CMT)

Manila Faul	Mw	Length (km)	Width (Km)	Dislocation (m)	Depth (km)
Total	9.35	990	200	20	40

The earthquake parameters of Manila Fault






Fault distriputation along Manila Trench. (Map provided by USGS)


Fault distriputation along Manila Trench used in present study.

Initial free surface elevation




Initial free-surface profile (Left) and three cross-section profiles (Right)


Bathymetry of Taiwan



Initial free surface elevation




Initial free-surface profile (Left) and three cross-section profiles (Right)




The maximum water-level rise.

Maximum free surface elevation




Maximum free-surface elevation and inundation area on Grid 3A

Maximum free surface elevation 2




Maximum free-surface elevation and inundation area on Grid 3B

Maximum free surface elevation 3




Maximum free-surface elevation on Grid 2


Why the seawall failed?





3月13日、外媒公布海嘯在日本登時瞬期期片。園館3月11日、海嘯衛上日本宮古市岸邊的





Tsunami hazard mitigation strategy

- 3D dynamic calculation is important in the hazard mitigation. Especially for the sensitive facilities such as the nuclear power plan, airport, etc.
- By incorporating with the earthquake early warning system and pre-calculated 2D and 3D results, the active hazard mitigation is able to provide useful information for the near-source tsunami with little warning time.
- The 2D+3D calculations are time and storage consuming. Assist from the gird system is needed.